

For every step you take there's a Carpenter Underlay

GreenStep



Classified to BS 5808: 1991 (2005)
General Domestic
Roll Length: 11m min
Roll Width: 137cms ±1%
15m² ±1%
Density: 75kg/m³ +5% -0%
Roll weight: 10Kg ±5%
Thickness: 8mm ± 5%
Classified to BS 4790:1987(2003)
Hot Metal Nut Test: Low Radius
Thermal Resistance: 2.13 Tog
Decibel Reduction Delta Lw: 34db



PRODUCT

General Domestic use bonded polyurethane underlay.
Specialised facing and backing laminate.

MARKET

General Domestic use in all living areas.

- Carpenter underlays add luxury and comfort and they protect your new carpet against premature wear. They are guaranteed for the lifetime of the carpet.
- Carpenter underlays are manufactured in Glossop, Derbyshire, UK using recycled PU foam and are recyclable.
- Carpenter underlays are permeable and may be laid over a wood block floor.
- Because they give such excellent insulation, Carpenter underlays are not suitable for underfloor heating.



CARPENTER

For further details contact:

Carpenter Ltd, Dinting Lodge Industrial Estate, Glossop, Derbyshire, SK13 6LE.

Tel: +44 (0)1457 861141 • Fax: +44 (0)1457 863242

Email: glossop.sales@carpenter.com Web: www.carpenter.ltd.uk